

QUOTATION


Name work : Repairing / Replacement of damaged street light at Environmental building, Type-2,3 & 6, Multistore apartment , Old SBRA and Old sport complex and other associated works as per enclosed Day to Day complaints.

S.N	Description	Qty	Unit	Rate (In words & figures)	Amount
1	S & F of following rating & poles 240 volts 'C' curve 10 kA MCB in the existing MCB DB complete with connection, testing & commissioning etc as reqd.				
a)	Single Pole (5A to 32A)	1.00	Nos.		
b	Single Pole (40A to 63A)	1.00	Nos.		
2	Supplying and fixing of 32 mm dia X 2.00 metres long G.I. pipe (medium class) bracket for mounting of fluorescent / HPMV / HPSV street light fitting on pole including bending the pipe to the required shape, 2 nos 40 mm X 3 mm flat iron clamps with nuts, bolts and washer, painting the flat iron with primer and finish paint etc. as required	1.00	Nos.		
3	Digging cable trench/lifting brick/s and cable for locating fault and refilling the trench, ramming & making good the same as reqd.	40.00	Mtr.		
4	Dismantling and refixing brass compression type gland up to 35 sq. mm. cable	14.00	Nos.		
5	Locating fault in the cable lines with meggar etc and rectifying removing & restoring the same and making good the damages etc as required.				
a	upto 35 sqmm	10.00	Nos.		
6	Fixing cross arm / street light brakcet/street light fitting from pole complete as required.	5.00	Nos.		

S.N	Description	Qty	Unit	Rate (In words & figures)	Amount
7	Dismantling cross arm / street light brakcet/street light fitting from pole complete as required.	13.00	Nos.		
8	Dismantling,repairing cleaning and commissioning of all type of street light fitting on pole/ walls etc. as reqd.	5.00	Nos.		
9	S/F testing commissioning of street light Luminures.ENDURA CITYLITE PLAT INUM PLUS 35W LED Energy saving and environmental friendly long life LED street light made up of pressure die cast aluminium housing with high power LED as lighting source and lens embedded PC cover having IP65 protection and Impact resistance of IK07 with 10KV Built-in Surge Protection Device.,make:havells or its equivalent, on the existing street light pole complete as required.	6.00	Nos.		
10	Supplying and drawing of following sizes of FR PVC insulated copper conductor, 3 core round cable of following size in the existing surface/ recessed steel/ PVC conduit as required.				
a	1.5 Sq.mm	30.00	Mtrs.		
11	Supply and installation of 400mm sweep AC 230/250 volts, 50 Hz wall mounting revolving fan with brackets etc complete.	2.00	Nos.		
12	Dismantling damaged switch/DB/KWH meter/ all type fitting / ceiling fan / Exhaust fan/ Wall Fan / pole fuse box/TPN switches metal helide box with MCB/Pole fuse box and depositing in the section store.	2.00	Nos.		

S.N	Description	Qty	Unit	Rate (In words & figures)	Amount
13	Supplying,fixing,testing commissioning of garden light 40W LED postop lantern Luminures. New generation, post-top, energy saving, environmental friendly, long life aesthetically designed with symmetrical light distribution, spun aluminium landscape luminaire with high power LEDs as light source make:Crompton Greaves Havells or its equivalent on the existing pole complete as required.	3.00	Nos.		
14	S&F, connecting and commissioning looping type cable end control box with MS sheet of 16 SWG of size 200 mm x 200 mm x 125 mm having 1 no. 6amp to 32 amp SPMCB 250 volt and 2 nos. brass neutral link 12.5 mm square rod 6 way approx. 60 mm long and fixed on 5 mm thick bakelite sheet. Box shall have almirah type hing and panel key type lock front door duly painted with earthing strud etc. complete as required.	1.00	Nos.		
15	Fabrication, supplying & fixing of box of required size made out of 2mm thick CRCA sheet duly powder coated & openable from top-bottom or front required & fixing the same complete as required.	3.00	Kg		

Total Rs.


राघवेंद्र सिंह
RAGHVENDRA SINGH
 अधिरक्षणी अभियंता (वि०) E.E. (Elect.)
 सं० वि० वि०, पा० वि० संस्थान, कानपुर
 I.W.D., J.J.T., Kanpur
