

## भारतीय प्रौद्योगिकी संस्थान कानपुर Indian Institute of Technology Kanpur

Dr. Thiruvancheril G. Gopakumar

Assistant Professor Department of Chemistry, IIT Kanpur Kanpur 208016 UP, India

\*\* +91 (0)5122596830 e-mail: <a href="mailto:gopan@iitk.ac.in">gopan@iitk.ac.in</a>

URL: http://home.iitk.ac.in/~gopan/index.htm

Department office: \$\frac{1}{25}\$ +91 (0)512259 7637 \$\frac{1}{25}\$ +91 (0)512259 6806

10 September 2015

Inquiry No. IITK/CHM/TGG/2015/004

Last date: 17<sup>th</sup> September, 2015 till 1:00 PM

Sub.: Request for quotation for ULTRA LOW NOISE CURRENT AMPLIFIER for spectroscopy

Dear Sir/Madam

Kindly send us sealed quotations for the following items. Preferably, provide us a combined quotation for both items. Quotations should be addressed to **Dr. Thiruvancheril G. Gopakumar, Department of Chemistry, IIT Kanpur 208016**, and must reach on or before 17<sup>th</sup> September, 2015 till 1:00 PM.

Thanking you

Thiruvancheril G. Gopakumar

## Specifications for ULTRA LOW NOISE CURRENT AMPLIFIER for spectroscopy

## 1) ULTRA LOW NOISE CURRENT AMPLIFIER

Gain: Transimpedance 1 x 10<sup>9</sup> V/A (Accuracy ± 1%)
Input: Input Noise Current < 7 fA/VHz (@ 1 kHz)</li>
Input Noise Voltage < 10 nV/VHz (@ 1 kHz)</li>
Offset Current Compensation < ± 3 nA</li>

Max. Input Current ± 10 nA (Linear Amplification)

• Freuency Response: Lower Cut-Off Frequency DC

Upper Cut-Off Frequency 4 kHz

Rise time < 100  $\mu$ s Gain Flatness  $\pm$  0.1 dB

• Output: Output Voltage ± 10 V

Output Impedance 50  $\Omega$ 

Max. Output Current ± 10 mA (Linear Amplification)

Supply ± 15 V
Operating Temperature 0 ... +60 °C

## **Terms and Conditions:**

1. Price should be CIP Delhi/Kanpur

2. Warranty: 1 year or more